



Ultra-Short-Throw Lens for 3-Chip DLP™ Projectors

ET-D3LEU100

Project in tight spaces from very short throw-distances. With zero offset capability, these two lens options widen the versatility of Panasonic's 3-Chip DLP™ lineup.

Key Features

Minimize Throw Distance, Increase Flexibility

Wide-Range Adjustment After Projector Installation

Lens Design Delivers an Unobstructed View

ET-D3LEU100

<https://ap.connect.panasonic.com/id/en/et-d3leu100>

| | |
|----------------------------------|---|
| Lens type | Ultra-Short-Throw Lens |
| F Value | 2.5 |
| Focal Length | (f) 8.0 mm (5/16") |
| Screen Size | 200-600 inches |
| Throw ratio 4K+ | 0.397:1 |
| Throw ratio WUXGA | 0.370:1 |
| Throw ratio SXGA+ | 0.401:1 |
| Lens-shift*1 Vertical | ±59 % |
| Lens-shift*1 Horizontal | +29 % - -5 % |
| Zoom | No |
| Dimensions (W×H×D) | 275 x 154 x 428.7 mm (10 13/16" x 6 1/16" x 16 7/8") |
| Weight | Approx. 8.0 kg (17.6 lbs) |
| Compatible projectors | RQ32K/RZ31K Series/RQ22K/RZ21K Series/RQ13K/RZ12K Series/DZ21K2 Series/DZ13K Series |
| Note | *1 Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information: https://panasonic.net/cns/projector/calculator/tdc/ . For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value. |
| Throw ratio WXGA | 0.413:1 |