



Ultra-Short-Throw Lens for 3-Chip DLP™ Projectors

ET-D3LEU100

Project in tight spaces from very short throw-distances. With zero offset capability, these two lens options widen the versatility of Panasonic's 3-Chip DLP™ lineup.

Key Features

Minimize Throw Distance, Increase Flexibility

Wide-Range Adjustment After Projector Installation

Lens Design Delivers an Unobstructed View

ET-D3LEU100

<https://ap.connect.panasonic.com/id/en/et-d3leu100>

Lens type	Ultra-Short-Throw Lens
F Value	2.5
Focal Length	(f) 8.0 mm (5/16")
Screen Size	200-600 inches
Throw ratio 4K+	0.397:1
Throw ratio WUXGA	0.370:1
Throw ratio SXGA+	0.401:1
Lens-shift*1 Vertical	±59 %
Lens-shift*1 Horizontal	+29 % - -5 %
Zoom	No
Dimensions (W×H×D)	275 x 154 x 428.7 mm (10 13/16" x 6 1/16" x 16 7/8")
Weight	Approx. 8.0 kg (17.6 lbs)
Compatible projectors	RQ32K/RZ31K Series/RQ22K/RZ21K Series/RQ13K/RZ12K Series/DZ21K2 Series/DZ13K Series
Note	*1 Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information: https://panasonic.net/cns/projector/calculator/tdc/ . For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.
Throw ratio WXGA	0.413:1