





## AK-HRP250

<https://ap.connect.panasonic.com/m/y/en/ak-hrp250>

<b>General -&gt; Power Supply</b>	12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply)
<b>General -&gt; Power Consumption</b>	0.51 A (Power supply from camera: 10 V - 16 V DC) 0.15 A (PoE power supply)
<b>General -&gt; Operating Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>General -&gt; Operating Humidity</b>	90 % or less
<b>General -&gt; Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>General -&gt; Weight</b>	Approx. 1.4 kg (3.08 lb)
<b>General -&gt; Dimensions</b>	W 92 mm x H 308 mm x D 67 mm (3-5/8 inches x 12-1/8 inches x 2-5/8 inches)
<b>General -&gt; Camera/CCU Control</b>	Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected) <sup>*1</sup> , 12 V DC (when camera connected) <sup>*1</sup>
<b>General -&gt; Maximum Cable Length</b>	When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft)
<b>Input/Output -&gt; CCU connector</b>	10-pin, male x 1
<b>Input/Output -&gt; PREVIEW connector</b>	9-pin, female x 1
<b>Input/Output -&gt; LAN connector</b>	RJ-45 x 1 (equipped with a robust LAN terminal connector)
<b>Footnote Description</b>	Can be provided from CCU.