



**Advanced multi-point HD Video conferencing system, expandable up to a 24-Site Connection. Standard system comes with 16 site connection, this can be expanded to 24 sites with a licence Dual Network Multi Device Triple Monitor**

## **KX-VC2000**

Panasonic KX-VC2000 HD Visual Communication System allows efficient communication and information sharing between up to 24 sites with minimum initial setting costs. The HDVC System incorporates Panasonic's high-quality image and sound technologies.

### **Key Features**

Multi-site videoconference with up to 24 locations.

Easy operation and management: Dual Streaming and triple Monitor support at the hosting site, Optimum screen layout between all participants and presenter's screens, Remote Camera Control.

Smooth 2-way conversation with Broadband Stereo Full Duplex Audio and unique Echo Canceller technology.

AV-QoS Technology H.264 high-profile codec for high image compression efficiency

Expandability with the purchase of HDVC activation keys and optional accessories ● ALM Multicast (one-way transmission) ● Add 4 sites Connection ● Mobile Control License ● NAT Traversal Cloud Service. Link up signals from Android, iOS and Windows PC ● Pe

KX-VC2000

<https://ap.connect.panasonic.com/p/h/en/kx-vc2000>

<b>Communication Protocol</b>	SIP, H.323
<b>Video Compression Method</b>	H.261 (Main Stream only), H.263, H.263+, H.263++ (reception only), H.264 High Profile, H.264 Baseline Profile
<b>Audio Compression Method</b>	G.711 $\mu$ -law, A-law (3.4 kHz@64 kbps)G.722 (7.0 kHz@64 kbps)G.722.1 (7.0 kHz@32 kbps)G.722.1 Annex C (14.0 kHz@48 kbps/24 kbps)MPEG-4 AAC-LD Mono (7.0 kHz@32 kbps, 14.0 kHz@64 kbps,22.0 kHz@96 kbps)MPEG-4 AAC-LD Stereo (14.0 kHz@64 kbps, 22.0 kHz@96 kbps)
	No. of Channels:G.711/G.722/G.722.1/G.722.1 Annex C: 1MPEG-4 AAC-LD Mono: 1/MPEG-4 AAC-LD Stereo: 2
<b>Remote Camera Control</b>	H.224, H.281 (Zoom/Pan/Tilt/Preset)
<b>Dual Stream (Method)</b>	H.239 (H.323), BFCP (SIP)
<b>Dual Stream (No. of Displays)</b>	3 displays
<b>Dual Stream(Supported Resolution and Frame Rate)</b>	Main: Maximum 1080p 30 frames/sec. Sub: 1080p 30 frames/sec.
<b>Encryption</b>	SRTP (AES 128-bit), H.235 (AES 128-bit)
<b>Other</b>	H.460
<b>Communication Bandwidth</b>	256 kbps–24 Mbps
<b>Video Compatible Resolution</b>	176 x 144p, 352 x 240p, 352 x 288p, 512 x 288p, 640 x 480p, 704 x 480p, 704 x 576p, 768 x 432p, 800 x 600p  1024 x 768p, 1280 x 720p, 1280 x 768p, 1280 x 800p, 1920 x 1080p  *1 Varies according to device settings and the status of the network.
<b>Video Frame Rate</b>	Maximum 60 frames/sec. (When using H.264 1080p)
<b>Video Screen Display</b>	Full screen, Picture in Picture, Picture with Picture, Side by Side
<b>Audio</b>	Echo Canceller, Auto Gain Control, Stationary Noise Reduction, Lip Sync, Equalizer, Mic Mute
<b>Input/Output Terminals (Video Input Camera)</b>	HDMI Main $\times$ 1, HDMI Sub $\times$ 1  Input Resolution: 1280 $\times$ 720p, 1920 $\times$ 1080i, 1920 $\times$ 1080p
<b>Input/Output Terminals (Video Input PC)</b>	RGB $\times$ 1 (Mini D-sub 15pin), HDMI $\times$ 1*2  Input Resolution: VGA, SVGA, XGA, HD, WXGA, SXGA, FWXGA, WXGA+, WXGA++, UXGA, WSXGA+, Full HD  *2 HDCP is not supported.
<b>Input/Output Terminals (Video Output)</b>	HDMI $\times$ 2  Supported output resolutions: 1920 $\times$ 1080i, 1920 $\times$ 1080p  RCA $\times$ 1 (Component)  HDMI $\times$ 1 (For own site/recording video)
<b>Input/Output Terminals (Audio Input)</b>	Boundary Microphone (Digital Interface Type) $\times$ 1 (KX-VCA001) (Up to 4)  Boundary Microphone (Analogue Interface Type) $\times$ 1 (KX-VCA002) (Up to 1)  Stereo mini-plug*3 $\times$ 1 ( $\phi$ 3.5 mm)  RCA $\times$ 1 (Stereo)  *3 For 3-conductor stereo mini-plugs only.
<b>Input/Output Terminals (Audio Outputs)</b>	HDMI*4  Stereo mini-plug*3 $\times$ 1 ( $\phi$ 3.5 mm)  RCA $\times$ 1 (Stereo)  *3 For 3-conductor stereo mini-plugs only.  *4 Simultaneous voice audio output for HDMI1/HDMI2 is not supported.
<b>Input/Output Terminals (Network)</b>	RJ45 $\times$ 2 (1000BASE-TX Full Duplex)
<b>Input/Output Terminals (External Controller)</b>	RS-232C $\times$ 1 (Also used for maintenance)
<b>Input/Output Terminals (Other)</b>	USB 2.0*9 $\times$ 1 (Host Mode, Device Mode), Camera Control terminal $\times$ 1 (Not used)*9 Power supply capacity: 5 V/500 mA
<b>No. of Simultaneous Connections</b>	16 (Expandable to 24)
<b>Contents Sharing</b>	PC (RGB/HDMI), Sub video camera (HDMI Sub)
<b>USB Host Mode (USB Memory Device)</b>	Updating Software, Import (Contact List/Profile*10 /Configuration Data/Encryption Data/Startup screen/Multicast Tree List), Export (ContactList/Profile *10 /Configuration Data/Encryption Data/Multicast TreeList), Recording  *10 Available for the KX-VC1000 after KX-VCS314 expansion has been enabled.
<b>USB Device Mode</b>	USB Video Class: Version 1.0  USB Audio Class: Version 1.0
<b>Network Protocol</b>	TCP/IPv4, TCP/IPv6 *11, UDP/IPv4, UDP/IPv6 *11, DHCP, DNS, HTTP,HTTPS, TELNET, NTP  *6 Some features are not supported when using IPv6.
<b>Network Functions</b>	Packet resending (ARQ), Forward Error Correction (FEC), Adaptive Rate Control (ARC), Reorder, Packet Shaping, Arbitrary port setting, NAT support, encryption, IP Precedence/DiffServ support
<b>External Control</b>	Control via web browser/HTTP CGI, TELNET, RS-232C
<b>Connection Mode</b>	IP mode, NAT Traversal mode, IP / NAT Traversal Mode

<b>Dimensions (W x H x D)</b>	Approx. 320 mm × approx. × 270 mm × approx. 61 m (excluding projecting parts) (approx. 12 in × approx. 10 in × approx. ×2.4 in)
<b>Weight</b>	Approx. 3.4 kg (approx. 7.5 lb)
<b>Power Input</b>	AC 100–240 V, 50/60 Hz up to 1.0 A
<b>Power Consumption</b>	Maximum: 73 W, Instand by: 0.6 W
<b>DC Power Input</b>	DC 24 V, 3.0 A
<b>Operating Temperature</b>	0 °C – 40 °C (32 °F – 104 °F)
<b>Operating Humidity</b>	10 % – 90 % (non - condensing)