



**High placement quality and high throughput are the characteristics of Panasonic's NPM-DX, the next generation of smart pick and place equipment.**

## NPM-DX

The NPM-DX provides a greater line throughput, better quality and lower production cost featuring an autonomous line control, which guarantees a stable operation based on automatic functionality. This functionality in combination with the machine set up offers a labor-saving production with improved utilization. In combination with the Panasonic software environment and embedded into an Industry 4.0 philosophy, the user can expect a modern shop floor management system including various remote operation options, feeder setup navigation, component supply navigation etc. In total, the NPM-DX reduces downtimes and increase the line throughput. With 92 400 cph and a feeder capacity for up to 136 reels, the NPM-DX is the ideal solution to meet the expectation of an evolving electronics assembly industry. The NPM-DX can process PCB sizes of up to 510 x 590 mm and place large connectors (up to 150 x 25mm) and other components (up to 120 x 90mm). This and other features make the NPM-DX the best solution for high volume-mix manufacturing.

### Key Features

---

92 400 cph and feeding with up to 136 reels

---

Ready for line automatization

---

Available APC system

---

Integrated floor management

---

Lowest total cost of ownership (TCO) with maintenance services

## NPM-DX

<https://ap.connect.panasonic.com/p/h/en/npm-dx>

<b>Model Number</b>	NPM-DX
<b>PCB dimensions (mm)</b>	Single-lane mode: L 50 × W 50 ~ L 510 × W 590 Dual-lane mode: L 50 × W 50 ~ L 510 × W 300 *When the long spec. conveyor is selected
<b>PCB exchange</b>	2.1 s (L 275 mm or less); 4.8 s (L 275 mm or over to L 460 mm or less)  *May differ depending on PCB specifications. *When the short spec. conveyor is selected
<b>Electric Source</b>	3-phase AC 200, 220, 380, 400, 420, 480 V 5.0 kVA
<b>Pneumatic Source</b>	Min.0.5 MPa, 200 L/min (A.N.R.)
<b>Placement Head max Speed</b>	Lightweight 16-nozzle head V2 (Per head): 46 200 cph (0.078 s/ chip)  Lightweight 8-nozzle head (Per head): 24 000 cph (0.150 s/ chip)  4-nozzle head (Per head): 8 500 cph (0.424 s/ chip) 8 000 cph (0.450 s/ QFP)
<b>Placement Head Placement Accuracy (Cpk<sub>≥1</sub>)</b>	Lightweight 16-nozzle head V2 (Per head): ±25 μm/Square chip  Lightweight 8-nozzle head (Per head): ±25 μm/ Square chip; ±40 μm/QFP □12 mm Under; ±25 μm/QFP □12 mm to □32 mm  4-nozzle head (Per head): ±20 μm/ QFP
<b>Placement Head Component Dimensions (mm)</b>	Lightweight 16-nozzle head V2 (Per head): 0201 component / 03015 component; 0402 component to L 6 x W 6 x T 3  Lightweight 8-nozzle head (Per head): 0402 component ~L 45 x W 45 or L 100 x W 40 x T 12  4-nozzle head (Per head): 0603 chip ~ L 120 x W 90 or L 150 x W 25 x T 30
<b>Component Supply Taping</b>	Lightweight 16-nozzle head V2 (Per head): Tape: 4 / 8 / 12 / 16 / 24 / 32 / 44 / 56 mm  Lightweight 8-nozzle head (Per head): Tape: 4 / 8 / 12 / 16 / 24 / 32 / 44 / 56 mm  4-nozzle head (Per head): Tape: 4 ~56 / 72 / 88 / 104 mm