



**1-Chip DLP™ Projectors Evolve with 15,000 lm on AC 100–240 V, Unlocking Ideas for Novel Experiences**

## PT-REZ15

The next-generation PT-REZ15 1-Chip DLP™ 4K Laser Projector is designed to streamline productions and expand the endless possibilities of entertainment by delivering exceptional, highly engaging immersive experiences with up to 15,000lm brightness, 4K resolution, and 240 Hz projection capability.

### Key Features

Spectacular Visuals on a Grand Scale

Effortless Workflow and Expanded Capabilities

Supremely Reliable Maintenance-Free Operation



PT-REZ15

<https://ap.connect.panasonic.com/p/h/en/pt-rez15>

<b>Projector type</b>	1-Chip DLP™ projector
<b>Display method</b>	DLP™ chip x 1, DLP™ projection system
<b>Display Device -&gt; Panel size</b>	0.8 in. diagonal (16:10 aspect ratio)
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1920 x 1200 pixels)
<b>Light source</b>	Laser diode
<b>Light output *1 *2 *3</b>	15,000 lm
<b>Light output (ANSI) *4</b>	15,000 lm
<b>Light output (Center) *5</b>	PT-REZ15 : 15,500 lm (Center)PT-REZ12 : 12,400 lm (Center)PT-REZ10 : 10,300 lm (Center)PT-REZ80 : 8,200 lm (Center)
<b>Time until light output declines to 50 %</b>	20,000 hours [NORMAL]
<b>-&gt; NORMAL *6</b>	
<b>Time until light output declines to 50 %</b>	24,000 hours[ECO]
<b>-&gt; ECO *6</b>	
<b>Time until light output declines to 50 %</b>	20,000 hours [QUIET]
<b>-&gt; QUIET *6</b>	
<b>Resolution</b>	WUXGA (1920 x 1200 pixels)
<b>Contrast Ratio (typ.) *3</b>	25,000:1 (Full On/Full Off, Dynamic Contrast [3])
<b>Screen size (diagonal)</b>	70–700 inches (with supplied lens)
<b>Center-to-corner zone ratio *3</b>	90%
<b>Lens</b>	Optional powered zoom/focus lenses
<b>Lens shift -&gt; Vertical(from center of screen)</b>	±60 % (with ET-C1W400/W500/S600/T700/T800), ±50 % (with ET-C1W300/U100), +88 % (with ET-C1U200)
<b>Lens shift -&gt; Horizontal(from center of screen)</b>	±29 % (with ET-C1W400/W500/S600/T700/T800), ±23 % (with ET-C1W300/U100)
<b>Keystone correction range</b>	Vertical: ±40 ° (±5 ° with ET-C1U100; ±10 ° with ET-C1W300; ±16 ° with ET-C1W400; ±22 ° with ET-C1W500), Horizontal: ±40 ° (±3 ° with ET-C1U100; ±5 ° with ET-C1W300; ±10 ° with ET-C1W400; ±15 ° with ET-C1W500)
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals -&gt; HDMI™ IN</b>	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)*5
<b>Terminals -&gt; DisplayPort™ IN</b>	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)*5
<b>Terminals -&gt; MULTI PROJECTOR SYNC IN</b>	BNC x 1
<b>Terminals -&gt; MULTI PROJECTOR SYNC OUT</b>	BNC x 1
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals -&gt; SERIAL OUT</b>	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
<b>Terminals -&gt; REMOTE 1 IN</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Terminals -&gt; REMOTE 1 OUT</b>	M3 stereo mini-jack x 1 for link control (for wired remote control)
<b>Terminals -&gt; REMOTE 2 IN</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Terminals -&gt; DC OUT</b>	USB Type A x 1 (for power supply, DC 5 V, 2 A)
<b>Terminals -&gt; USB TYPE A</b>	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory
<b>Terminals -&gt; SLOT</b>	Open slot for function boards, Intel® SDM standard SLOT-compatible
<b>Protocol versions</b>	IPv4、IPv6*6
<b>Power supply</b>	AC 100–240 V, 50/60 Hz
<b>Maximum power consumption *7</b>	1,090 W (11.5–4.7 A) (1,100 VA) (Power consumption is 1,040 W at AC 200–240 V)
<b>On-mode power consumption(Operating mode) -&gt; Normal *8</b>	[NORMAL] 945 W (AC 100–120 V), 900 W (AC 200–240 V)
<b>On-mode power consumption(Operating mode) -&gt; Eco *8</b>	[ECO] 730 W (AC 100–120 V), 700 W (AC 200–240 V)
<b>On-mode power consumption(Operating mode) -&gt; Quiet *8</b>	[QUIET] 725 W (AC 100–120 V), 695 W (AC 200–240 V)
<b>Cabinet materials</b>	Molded plastic
<b>Filter</b>	No
<b>Operation noise -&gt; Normal *3</b>	42 dB [NORMAL]
<b>Operation noise -&gt; Eco *3</b>	42 dB [ECO]
<b>Operation noise -&gt; Quiet *3</b>	38 dB [QUIET]
<b>Dimensions (W x H x D)</b>	PT-REZ15: 498 x 212 x 648 mm (19 19/32" x 8 11/32" x 25 1/2") (With feet at shortest position)PT-REZ15L: 498 x 212 x 538 mm (19 19/32" x 8 11/32" x 21 3/16") (With feet at shortest position)
<b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b>	498 mm (19 19/32")
<b>Dimensions -&gt; Height (including protruding parts)</b>	212 mm (8 11/32")
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	538 mm (21 3/16")
<b>Weight</b>	PT-REZ15: Approx. 28.7 kg (63.27 lbs) (with supplied lens)PT-REZ15L: Approx. 27.0 kg (59.52 lbs) (without lens)
<b>Operating environment -&gt; Operating temperature *11</b>	0–45 °C (32–113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10–80 % (no condensation)
<b>Applicable software</b>	Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™

<b>Control function via LAN</b>	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PJLink™ (Class 2)
<b>Body Colour</b>	Black
<b>Gross Dimensions (W x H x D in mm)</b>	REZ15BEJ: Approx. 651 x 375 x 838 mm REZ15BE: Approx. 639 x 355 x 826 mm
<b>Gross Weight (Kg)</b>	REZ15BEJ: 36.7 kg (81.0 lbs) REZ15BE: 34.6 kg (76.4 lbs)
<b>NFC</b>	Yes
<b>EAN</b>	REZ15BEJ: 5025232960941 REZ15BE: 8887549861192
<b>Terminals -&gt; SDI IN</b>	—
<b>Terminals -&gt; DVI-D IN</b>	—
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	—
<b>Active 3D</b>	No
<b>SDM</b>	Yes
<b>Footnote Description</b>	<ol style="list-style-type: none"> <li>1. This is the value when the Zoom Lens (Model No.: ET-C15600) is used. The value varies depending on the lens.</li> <li>2. When [OPERATING MODE] is set to [NORMAL].</li> <li>3. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.</li> <li>4. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</li> <li>5. Average light-output value of all shipped products measured at the center of the screen.</li> <li>6. Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of airborne particulate matter. The estimated time until light output declines to 50 % varies depending on the environment.</li> <li>7. 4K signals are converted to WUXGA (1920 x 1200 pixels).</li> <li>8. Optional AJ-WM50 Series Wireless Module is not compatible with IPv6.</li> <li>9. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</li> <li>10. This value has included a maximum power consumption of 80 W when using a function board.</li> <li>11. Average value. May differ depending on the actual unit.</li> <li>12. When the optional AJ-WM50 Series wireless module is attached, the operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C(32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).</li> <li>13. Excluding the REZ15. Software replaced with equivalent functions in the Web Control UI.</li> </ol>