

## Revitalize Sustainability and Image Quality in Classrooms and the Workplace

### PT-MZ882

The Series features PT-MZ882 (8,200 lm11), PT-MZ782 (7,500 lm11), and PT-MZ682 (6,500 lm) WUXGA models with a refined Multi-Laser Drive Engine for the optimal balance of high brightness, vivid colour, and low-maintenance operation. \*1 Measurement, measuring conditions, and method of notation are all compliant with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.

#### Key Features

Eco-Conscious Design Includes Recycled Materials

Bright and Sharp for Comfortable Visibility

A Streamlined Workflow and Efficient UX



<b>Projector type</b>	LCD projector
<b>Display method</b>	Transparent LCD panel (x 3, R/G/B)
<b>Display Device -&gt; Panel size</b>	19.3 mm (0.76 in) diagonal (16:10 aspect ratio)
<b>Display Device -&gt; Drive method</b>	Active matrix method
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1920 x 1200 pixels)
<b>Light source</b>	Laser diodes
<b>Light output&lt;sup&gt; *1&lt;/sup&gt;&lt;sup&gt; *2&lt;/sup&gt;&lt;/sup&gt;</b>	8,200 lm
<b>Light output (ANSI)&lt;sup&gt; *3&lt;/sup&gt;&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	8,200 lm
<b>Time until light output declines to 50 %&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	20,000 hours [NORMAL]
<b>-&gt; NORMAL&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	
<b>Time until light output declines to 50 %&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	24,000 hours [ECO]
<b>-&gt; ECO&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	
<b>Time until light output declines to 50 %&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	20,000 hours [QUIET]
<b>-&gt; QUIET&lt;sup&gt; *4&lt;/sup&gt;&lt;/sup&gt;</b>	
<b>Resolution</b>	WUXGA (1920 x 1200 pixels)
<b>Contrast Ratio (typ.)&lt;sup&gt; *2&lt;/sup&gt;&lt;/sup&gt;</b>	3,000,000:1 (Full On/Full Off)
	(When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1] or [2]. HDMI™ signal input)
<b>Screen size (diagonal)</b>	1.02–10.16 m (40–400 in), 1.52–10.16 m (60–400 in) with the ET-ELW22, 2.54–10.16 m (100–400 in) with the ET-ELU20, 16:10 aspect ratio
<b>Center-to-corner zone ratio&lt;sup&gt; *2&lt;/sup&gt;&lt;/sup&gt;</b>	85%
<b>Lens</b>	Powered zoom (throw ratio 1.61–2.76:1), powered focus F = 1.7–2.3, f = 26.8–45.5 mm (for supplied lens; optional lenses also available)
<b>Lens shift -&gt; Vertical(from center of screen)</b>	±67 % (powered), ±60 % (with ET-ELW22), ±50 % (with ET-ELU20) (TBD)
<b>Lens shift -&gt; Horizontal(from center of screen)</b>	±35 % (powered), ±30 % (with ET-ELW22), ±24 % (with ET-ELU20) (TBD)
<b>Keystone correction range</b>	Vertical: ±25 ° (±22 ° with ET-ELW21/ET-ELW22); (±25 ° with ET-ELW20/ET-ELT22/ET-ELT23); (±5 ° with ET-ELU20), Horizontal: ±30 ° (±15 ° with ET-ELW21/ET-ELW22); (±30 ° with ET-ELW20/ET-ELT22/ET-ELT23); (0 ° with ET-ELU20)
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals -&gt; HDMI&lt;sup&gt;™&lt;/sup&gt; IN</b>	HDMI™ x 3 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*4), CEC supported
<b>Terminals -&gt; COMPUTER IN ( D-SUB 15pin )</b>	D-sub HD 15-pin (female) x 1 (RGB/Y/P <sub>B</sub> /Y/C <sub>B</sub> /C <sub>R</sub> )
<b>Terminals -&gt; COMPUTER OUT ( D-SUB 15pin )</b>	D-sub HD 15-pin (female) x 1 (RGB/Y/P <sub>B</sub> /Y/C <sub>B</sub> /C <sub>R</sub> )
<b>Terminals -&gt; AUDIO IN(M3 Stereo Mini Jack)</b>	M3 stereo mini-jack x 1
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	M3 stereo mini-jack x 1
<b>Terminals -&gt; MULTI PROJECTOR SYNC IN</b>	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
<b>Terminals -&gt; MULTI PROJECTOR SYNC OUT</b>	D-sub 9-pin (male) x 1 for link control
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
<b>Terminals -&gt; SERIAL/MULTI-PROJECTOR SYNC IN</b>	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
<b>Terminals -&gt; SERIAL/MULTI-PROJECTOR SYNC OUT</b>	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
<b>Terminals -&gt; REMOTE 1 IN</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Terminals -&gt; REMOTE 2 IN</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p*4 *5 signal input)
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)
<b>Terminals -&gt; DC OUT</b>	USB Type A x 1 (for power supply, DC 5 V, 2 A)
<b>Power supply</b>	AC 100–240 V, 50 Hz/60 Hz
<b>Maximum power consumption&lt;sup&gt; *7&lt;/sup&gt;&lt;/sup&gt;</b>	465 W (5.1–2.5 A) (490 VA)
	(Power consumption is 445 W at AC 200–240 V) (TBD)
<b>On-mode power consumption(Operating mode) -&gt; Normal&lt;sup&gt; *7&lt;/sup&gt;&lt;/sup&gt;</b>	[NORMAL] 410 W (AC 100–120 V), 390 W (AC 200–240 V) (TBD)
<b>On-mode power consumption(Operating mode) -&gt; Eco&lt;sup&gt; *7&lt;/sup&gt;&lt;/sup&gt;</b>	[ECO] 295 W (AC 100–120 V), 280 W (AC 200–240 V) (TBD)
<b>On-mode power consumption(Operating mode) -&gt; Quiet&lt;sup&gt; *7&lt;/sup&gt;&lt;/sup&gt;</b>	[QUIET] 290 W (AC 100–120 V), 275 W (AC 200–240 V) (TBD)
<b>Cabinet materials</b>	Molded plastic

<b>Filter</b>	Included
<b>Estimated filter maintenance cycle</b>	Approx. 20,000 hours
<b>Operation noise -&gt; Normal<sup>2</sup></b>	34 dB [NORMAL]
<b>Operation noise -&gt; Eco<sup>2</sup></b>	34 dB [ECO]
<b>Operation noise -&gt; Quiet<sup>2</sup></b>	26 dB [QUIET]
<b>Dimensions (W x H x D)</b>	561 x 224 x 439 mm (22 3/32" x 8 13/16" x 17 9/32") (With legs at shortest position, including lens and protruding parts)
<b>Dimensions -&gt; Width (including protruding parts)</b>	561 mm (22 3/32")
<b>Dimensions -&gt; Height (including protruding parts)</b>	224 mm (8 13/16")
<b>Dimensions -&gt; Depth (including lens)</b>	439 mm (17 9/32")
<b>Weight<sup>8</sup></b>	Approx. 18.6 kg (41.0 lbs) (with supplied lens)
<b>Operating environment -&gt; Operating temperature<sup>9</sup></b>	0-45 °C (32-113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10-80 % (no condensation)
<b>Applicable software</b>	Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Smart Projector Control for iOS/Android™, Geometry Manager Pro <sup>9</sup>

#### Footnote Description

When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL].

Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.

Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.

Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2]). Estimated time until light output declines to 50 % varies depending on environment.

4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection.

YP<sub>B</sub>P<sub>R</sub> 4:2:0 format only for 4K/60p and 4K/50p signals input via DIGITAL LINK.

Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).

Average value. May differ depending on the actual unit.

Note that the projector cannot be used at altitudes 2,700 m (8,858 ft) or higher above sea level. In the following operating environments, light output may be reduced to protect the projector: when the projector is used at altitudes below 700 m (2,297 ft) and ambient temperature is 36 °C (97 °F) or higher; when the projector is used at altitudes between 700 m (2,297 ft) and 1,400 m (4,593 ft) exclusive and ambient temperature is 34 °C (93 °F) or higher; when the projector is used at altitudes between 1,400 m (4,593 ft) and 2,100 m (6,890 ft) exclusive and ambient temperature is 32 °C (90 °F) or higher; and when the projector is used at altitudes between 2,100 m (6,890 ft) and 2,700 m (8,858 ft) exclusive and ambient temperature is 30 °C (86 °F) or higher.

This projector series does not support some functions available in Geo Pro software.

