Panasonic CONNECT



Zero Offset Ultra Short Throw Fixed-Focus Lens

ET-D3LEU100（for 3-Chip DLP™ Projectors）

Project in tight spaces from very short throw-distances. With zero offset capability, these two lens options widen the versatility of Panasonic's 3-Chip DLP™ lineup.

Panasonic CONNECT









ET-D3LEU100 (for 3-Chip DLP™ Projectors)

https://ap.connect.panasonic.com/ph/en/et-d3leu100for-3-chip-dlptm-projectors

Lens type	Ultra-Short-Throw Lens
F-number	2.5
Focal length (f)	8.0 mm (5/16″)
Screen size	200–600 inches
Throw ratio -> 4K+	0.397:1
Throw ratio -> WUXGA	0.370:1
Throw ratio -> SXGA+	0.401:1
Throw ratio -> WXGA	0.413:1
Auto Lens Identification function Compatible models	PT-RQ32K/RZ31K/RS30K/RQ25K/RZ24K/RQ18K/RZ17K/RZ14K/RQ22K/RZ21K/RS20K
Lens-shift -> Vertical *1	±59 % *1
Lens-shift -> Horizontal *1	+29 % – -5 % *1
Zoom	No
Dimensions -> (W)	275 mm(10 13/16″)
Dimensions -> (H)	154 mm(6 1/16″)
Dimensions -> (D)	428.7 mm(16 7/8″)
Weight	Approx. 8.0 kg (17.6 lbs)
Applicable projectors *2	RQ35K Series/RQ32K/RZ31K Series/RQ25K Series/RQ22K/RZ21K Series/RZ16K/RZ14K/RQ13K/RZ12K Series/DZ21K2 Series/DZ13K Series
Dimensions(WxHxD)	250 × 193 × 495 mm (9-27/32 × 7-19/32 × 19-1/2")
Footnote Description	* Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.