



The CCU supports UHD and HD simultaneous output while still having a compact size. HD mode enables output in 240p, 180p and 120p during normal filming.

AK-UCU600

With the AK-UCU600 Camera Control Unit (CCU), uncompressed longdistance transmission of 4K/HD video signals via optical fiber is supported. The AK-HRP1000GJ/1005GJ Remote Operation Panels (ROP) are equipped with a color LCD display that provides excellent visibility and functions for quick response. This system achieves high-quality video and excellent operability. In cases where power is supplied by the CCU, it is possible to transmit at a long distance of up to approx. 2,000 m between the camera and the CCU. The distance can be extended up to 10,000 m by providing a local power supply at the camera head and using general-purpose single mode optical fiber. Between the CCU and the ROP, in addition to a dedicated serial line, IP

Key Features

Contains a dual UHD 12G-SDI system, and supports 3G-SDI quad link and two-sample interleave

Optical fiber transmission of uncompressed video signals over a distance of approx. 2,000 m between camera and CCU

Supports TICO over SDI (4K over 3G-SDI) output (4K signal can be transferred by a conventional 3G-SDI cable)

Supports HDR/SDR simultaneous output and HDR BT2020/B709 simultaneous output

Supports IP streaming (100 Base-T)





AK-UCU600

<https://ap.connect.panasonic.com/p/h/en/ak-ucu600>