



**Compact screen printer with high efficiency
production and dual lanes**

SPV-DC

Compact screen printer with high efficiency production and dual lanes. Highly efficient production and dual lanes are realized in a compact size, providing the best functionality for your production configuration.

Key Features

High productivity in a compact package

High printing quality

SPV-DC

<https://ap.connect.panasonic.com/sg/en/spv-dc>

PCB dimensions (mm)	L 50 mm × W 50 mm to L 350 mm × W 300 mm
PCB exchange	13.0 s (6.5 s / PCB) Including transfer , positioning , recognition , each-time cleaning.* ¹ Printing & cleaning conditions : Our recommended conditions (PCB dimensions L 250 mm × W 165 mm)
Repeatability	2 Cpk ±5.0 μm 6 σ The repeatability of same PCB Equal to ±5.0 μm ± 3 σ (or ±2.5 μm ±1.5 σ)
Screen frame dimensions	L 736 mm × W 736 mm , L 650 mm × W 550 mm , L 550 mm × W 650 mm L 750 mm × W 750 mm , L 584 mm × W 584 mm* ²
Footnote Description	The contents above are standard specifications. Please contact us for details as it may differ depending on usage conditions. <ol style="list-style-type: none"> 1. PCB exchange time varies depending on the machine in the pre-process and the post process, the PCB size, the use of a PCB pressing-down unit and so forth. 2. For mask specifications, please see the specification.