Panasonic CONNECT

## Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

# ET-FMP50

Media Processor, compatible withAll Projector

**Key Features**

- Flexible Design Streamlines Installation
- Simple Yet High-Precision Adjustment
- Smooth and Continuous Content Playback

4K PROFESSIONAL

Panasonic CONNECT

# ET-FMP50

https://ap.connect.panasonic.com/sg/en/et-fmp50

| | |
|---|---|
| **Type** | Box-type |
| **Terminals -> HDMI™ OUT** | HDMI™ x 4, Audio signal: Linear PCM, 44.1 kHz/48 kHz, 16-bit, 2 channels |
| **Terminals -> AUDIO OUT(M3 Stereo Mini Jack)** | 3.5 mm stereo mini-jack |
| **Terminals -> LAN** | RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T,NDI® and Dante® (2 channels)*1 compatible |
| **Video format** | HAP*3 / H.264, 8-bit, 3840 x 2160 pixels, 60p,$YP_BP_R$ 4:2:0, 300 Mbps / H.265, 8-bit,18 million pixels (long side 7680 pixels or less), 60p, (including 7680 x 1920/60p, 4096 x 4096/60p), $YP_BP_R$ 4:2:0, 300 Mbps |
| **Max. video output resolution** | 3840 x 2160/60p x 1 or 1920 x 1080/60p x 4*2 |
| **Audio format** | AAC-LC, 16-bit, stereo |
| **Storage** | 4 TB |
| **Operating system** | Linux® |
| **Power supply** | AC 100–240 V, 50/60 Hz |
| **Maximum power consumption** | 64 W |
| **Weight** | Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord) |
| **ENVIRONMENT -> Operating Environment(Temperature)** | 0–40 °C (32–104 °F) |
| **ENVIRONMENT -> Operating Environment(Humidity) (No condensation)** | 10–80 % (no condensation) |
| **Terminals -> HDMI™ IN** | – |
| **Dimensions (W x H x D)** | Approx. 210 x 44 x 295 mm (8 9/32" x 1 23/32″ x 11 5/8″) (Excluding feet) |
| **Accessory Type** | Media Processor |
| **Applicable projectors** | All Projector |
| **Footnote Description** | 1. HAP Q content is not supported.<br>2. When four HDMI™ outputs are used simultaneously.<br>3. Compatible with HAP 1 and HAP Q. Please consult the spec file for detailed information.<br>4. For the ET-FMP20 (512 GB) and ET-SBFMP10 (512 GB), approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user.<br>5. The operating temperature range may differ according to the specific projector model paired with the ET-SBFMP10. |