



Ultra-short-throw lens, compatible with all Panasonic's 3-chip DLP™ projectors, enables large-screen projection from a short distance

ET-D75LE95

0.39:1 throw distance (WUXGA) Ultra Short-Throw Lens for 3-Chip DLP Projectors

Key Features

200-inch diagonal image can be produced from a distance of only about 1.5 m (5.0 ft) away from the screen

Lenses can be used in both vertical and horizontal edge blending

Throw ratio: 0.39:1 (for 4K+) / 0.36:1 (for the WUXGA & full HD resolution) / 0.39:1 (for the SXGA+ resolution) / 0.40:1 (for the WXGA resolution)

ET-D75LE95

<https://ap.connect.panasonic.com/sg/en/products/projectors/et-d75le95>

F-number	2.5
Focal length (f)	7.5 mm
Throw ratio -> WUXGA	Approx. 0.36:1
Throw ratio -> Full HD	Approx. 0.36:1
Throw ratio -> SXGA+	Approx. 0.39:1
Throw ratio -> WXGA	Approx. 0.40:1
Lens-shift -> Vertical	PT-RQ32K/RQ22K/RQ13K : up: 10%, down: 5% RT-RZ31K/RZ21K/RZ12K/DZ21K/DZ21K2/DZ13K/DZ10K : up: 5%, down: 7% PT-DZ16K/DZ16K2 : up: 13%, down: 8% RT-RS30K/RS11K/DS20K/DS20K2/DS12K : up: 7%, down: 7% PT-DW17K/DW17K2/DW11K : up: 18%, down: 0%
Lens-shift -> Horizontal	PT-RQ32K/RQ22K/RQ13K : left: 21%, right: 21% RT-RZ31K/RZ21K/RZ12K/DZ21K/DZ21K2/DZ13K/DZ10K : left: 12%, right: 12% PT-DZ16K/DZ16K2 : left: 19%, right: 19% RT-RS30K/RS11K/DS20K/DS20K2/DS12K : left: 8%, right: 8% PT-DW17K/DW17K2/DW11K : left: 13%, right: 27%
Dimensions -> (W)	ø154 mm (ø 6 1/16")
Dimensions -> (H)	ø154 mm (ø 6 1/16")
Dimensions -> (D)	463.5 mm (18 1/4")
Weight	Approx. 5.7 kg (12.6 lbs)
Applicable projectors	PT-RQ35K/RZ34K

PT-RQ32K

PT-RQ25K/RZ24K/RQ18K/RZ17K

PT-RQ22K

PT-RQ13K

PT-RZ31K/RS30K

PT-RZ21K/RS20K

PT-RZ16K

PT-RZ12K/RS11K

PT-DZ21K/DZ21K2/DS20K/DS20K2/DW17K/DW17K2/DZ16K/DZ16K2

PT-DZ13K/DS12K/DW11K/DZ10K/DZ8700/DZ110K/DS8500/DS1100K/DW8300/DW90K

Footnote Description

Note: Due to lens characteristics, some screen types may be subject to focusing problems or strong hot spots where large differences in brightness occur between the hot spots and surrounding areas. If this should occur, please ask a qualified technician or your dealer for solutions.