



“expressP2 drive” with High-Speed Thunderbolt™ 3 Interface Speeds up Video Production Workflow of 4K/high-frame-rate

AU-XPD3

Industry’s fastest offload device is designed for optimal performance with Panasonic’s expressP2 B series cards. The AU-XPD3 is equipped with a Thunderbolt3 interface, which is twice as fast as Thunderbolt2 and eight times faster than USB 3.0.

Key Features

Thunderbolt3 Interface

10 Gbps Transfer Speed

Offload 512 GB card in 7 minutes

Industry's fastest offload device

Daisychain to offload 2 x 512 GB cards in 8 minutes



AU-XPB3

<https://ap.connect.panasonic.com/sg/en/products/broadcast-proav/au-xpb3>

| | |
|--------------------------------|---|
| Power | DC 16 V 3.1 A |
| AC Adapter | Input: AC 100 V - 240 V, 50 Hz/60 Hz, 1.5 A - 0.8 A Output: DC 16 V, 3.75 A |
| Weight | Approx. 1.2 kg (2.65 lb) |
| Operating Temperature | 0 °C to 40 °C (32 °F to 104 °F) |
| Operating Humidity | 10 % to 85 % (no condensation) |
| Dimensions (W x H x D) | 126 mm x 62 mm x 216.5 mm (excluding protrusion) (4-31/32 inches x 2-7/16 inches x 8-17/32 inches) |
| Connector Configuration | USB Type-C connector x 2 |
| Card Slot | PC card slot x 1 (CardBus/PCI Express Base Specification) |