



“expressP2 drive” with High-Speed Thunderbolt™ 3 Interface Speeds up Video Production Workflow of 4K/high-frame-rate

AU-XPB3

Industry’s fastest offload device is designed for optimal performance with Panasonic’s expressP2 B series cards. The AU-XPB3 is equipped with a Thunderbolt3 interface, which is twice as fast as Thunderbolt2 and eight times faster than USB 3.0.

Key Features

Thunderbolt3 Interface

10 Gbps Transfer Speed

Offload 512 GB card in 7 minutes

Industries fastest offload device

Daisychain to offload 2 x 512 GB cards in 8 minutes

micro express
P2 P2



AU-XPd3

<https://ap.connect.panasonic.com/sg/en/au-xpd3>

Power Supply	DC 16 V 3.1 A
AC Adaptor	Input : AC 100 V - 240 V, 50 Hz/60 Hz, 1.5 A - 0.8 A
	Output : DC 16 V, 3.75 A
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating Humidity	10 % to 85 % (no condensation)
Weight	Approx. 1.2 kg (2.65 lb)
Dimensions	W 126 mm x H 62 mm x D 216.5 mm
	(4-31/32 inches x 2-7/16 inches x 8-17/32 inches)
	(excluding protrusion)
Connector Configuration	USB Type-C connector x 2
Card Slot	PC card slot x 1 (CardBus/PCI Express Base Specification)
PC Operation Requirements	Microsoft® Windows 10 (64 bit), macOS 10.12
PC Operation Requirements -> Main Memory	4 GB is recommended
PC Operation Requirements -> Interface	Thunderbolt™ 3 compliant