



## Simple plug & play collaboration solution

# TY-WPS1 series

“PressIT” is Panasonic’s Wireless Presentation System that allows easy screen collaboration with just a single press of a button. This elegant solution, designed to make collaboration quick and simple in meeting rooms, can connect up to 32 devices at one time, allowing users to present on screen or via a projector at the touch of a button..

### Key Features

For video and audio signals from PCs, iOS/Android, and other mobile devices

Two types of receivers: Set top box compatible with all displays and projectors, SDM board for SQ1 and SQE1 displays

Compatible with HDMI-CEC command control, linked operation with CEC compatible devices

Up to 4 simultaneous display sources, and up to 32 Transmitter simultaneous connections

No need for software and driver installation or network connection



## TY-WPS1 series

<https://ap.connect.panasonic.com/th/en/ty-wps1-series>

<b>Product</b>	Wireless Presentation System Basic Set
<b>Max. output resolution / Framerate</b>	Receiver : 1920 x 1080/60p, 3840 x 2160/30p (max.)
<b>Max. input resolution / Framerate</b>	Transmitter : 1920 x 1080/60p (max.)
<b>Number of simultaneous connections</b>	32
<b>Number of sources simultaneous on screen</b>	4
<b>Data Rate   Wired</b>	10/100/1000 (Mbps)
<b>Data Rate   Wireless</b>	Receiver : 867 Mbps (max.) Transmitter : 433 Mbps (max.)
<b>Frequency Band</b>	5 GHz (5180 MHz to 5240 MHz)
<b>Wireless Communication Standard</b>	Receiver : IEEE802.11/a/n/ac Transmitter : IEEE802.11ac
<b>Security</b>	WPA/WPA2 (AES)
<b>Reach (Max distance between transmitter and receiver)</b>	30 m (When the line of sight/wave conditions are good)
<b>Connection terminal</b>	Receiver : HDMI/USB-A (female)/RJ45 (LAN) Transmitter : HDMI/USB-A (female)/USB-A (male)
<b>Power Requirements</b>	Receiver : DC 5 V/2 A Transmitter : DC 5 V/0.9 A
<b>Power consumption (During image display)</b>	Receiver : 10 W Transmitter : 4.5 W
<b>Temperature   Operating</b>	Temperature: 0 °C to 35 °C (32 °F to 95 °F)
<b>Temperature   Storage</b>	Temperature: -20 °C to 60 °C (-4°F to 140°F)
<b>Dimensions (W x H x D)</b>	Receiver : 120 x 26 x 81 mm (4.71" x 1.03" x 3.19") ( Excluding antenna part ) Transmitter : 50.8 x 19.5 x 73.2 mm (2.00" x 0.80" x 2.86") (Excluding cables) Case : 151.3 x 41.6 x 198.0 mm (5.96" x 1.64" x 7.8")
<b>Weight</b>	Receiver : Approx. 181 g / 0.4 lbs Transmitter : Approx. 110 g / 0.3 lbs Case : Approx. 315 g / 0.7 lbs