



**Deliver More for Less with the World's Smallest and Lightest 20,000 lm 3-Chip DLP™ WUXGA Projector**

## PT-RZ24K

Deliver More for Less with the World's Smallest and Lightest 20,000 lm 3-Chip DLP™ WUXGA Projector

### Key Features

Compact Form-Factor Streamlines Workflow

Create an Engaging Visual Experience

Maintenance-free for Peace of Mind

3-Chip DLP™ WUXGA Laser Projector

20,000 Lumen Brightness





## PT-RZ24K

<https://ap.connect.panasonic.com/th/en/products/projectors/pt-rz24k>

<b>Projector type</b>	3-Chip DLP™ projector
<b>Display method</b>	DLP™ chip x 3, DLP™ projection system
<b>Display Device -&gt; Panel size</b>	20.3 mm (0.8 in) diagonal (16:10 aspect ratio)
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1920 x 1200 pixels) x 3
<b>Light source</b>	Laser diode
<b>Light output *1 *2 *3</b>	20,000 lm
<b>Light output (ANSI) *4</b>	20,000 lm
<b>Light output (Center) *5</b>	21,000 lm (Center)
<b>Time until light output declines to</b>	20,000 hours [NORMAL]
<b>50 % -&gt; NORMAL *6</b>	
<b>Time until light output declines to</b>	24,000 hours [ECO]
<b>50 % -&gt; ECO *6</b>	
<b>Time until light output declines to</b>	20,000 hours [QUIET]
<b>50 % -&gt; QUIET *6</b>	
<b>Resolution</b>	WUXGA (1920 x 1200 pixels)
<b>Contrast Ratio (typ.) *3</b>	25,000:1 (Full On/Full Off, Dynamic Contrast [3])
<b>Screen size (diagonal)</b>	1.78-25.40 m (70-1000 in), 1.78-15.24 m (70-600 in) with ET-D75LE8/ ET-D3LET80, 3.05-15.24 m (120-600 in) with ET-D75LE95, 5.08-15.24 m (200-600 in) with ET-D3LEU100/D3LEW200
<b>Center-to-corner zone ratio *3</b>	90%
<b>Lens</b>	Optional (no lens included with this model)
<b>Lens shift -&gt; Vertical (from center of screen)</b>	±66 % (52 % with ET-D75LE6/ET-D3LEW60, +71 % / +93 % with ET-D75LE95, ±66 % with ET-D3LEU100, ±57 % with ET-D3LEW200) (powered)
<b>Lens shift -&gt; Horizontal (from center of screen)</b>	±24 % (18 % with ET-D75LE6/ET-D3LEW60, ±14 % with ET-D75LE95, -25 % / +30 % with ET-D3LEU100, ±18 % with ET-D3LEW200) (powered)
<b>Keystone correction range</b>	Vertical: ±45 ° (± 40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals -&gt; HDMI™ IN</b>	HDMI x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*5)
<b>Terminals -&gt; DisplayPort™ IN</b>	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*5)
<b>Terminals -&gt; MULTI PROJECTOR</b>	—
<b>SYNC IN</b>	
<b>Terminals -&gt; MULTI PROJECTOR</b>	—
<b>SYNC OUT</b>	
<b>Terminals -&gt; MULTI SYNC IN / 3D BNC x 1</b>	
<b>SYNC 1 IN/OUT (dual purpose)</b>	
<b>Terminals -&gt; MULTI SYNC OUT / 3D SYNC 2 OUT (dual purpose)</b>	BNC x 1
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals -&gt; SERIAL OUT</b>	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
<b>Terminals -&gt; REMOTE 1 IN</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Terminals -&gt; REMOTE 1 OUT</b>	M3 stereo mini-jack x 1 for link control (for wired remote control)
<b>Terminals -&gt; REMOTE 2 IN</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, PJLink™(Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Terminals -&gt; DC OUT</b>	USB Type A x 1 (for power supply, DC 5 V, 2 A)
<b>Terminals -&gt; USB TYPE A</b>	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory
<b>Terminals -&gt; SLOT</b>	Open slot for function boards, Intel® SDM compatible
<b>Power supply</b>	AC 100 V-120 V / AC 200 V-240 V, 50 Hz/60 Hz (The maximum value of light output is limited to 15,000 lm or less when using the projector with AC 100 V to AC 120 V. Other limitations apply.*6)
<b>Maximum power consumption *7</b>	AC 200 V-AC 240 V : 1,470 W ( 1,520 VA) AC 100 V-AC 120 V : 1,060 W ( 1,090 VA )
<b>On-mode power consumption (Operating mode) -&gt; Normal *8</b>	[NORMAL] 1,310 W
<b>On-mode power consumption (Operating mode) -&gt; Eco *8</b>	[ECO] 1,020 W
<b>On-mode power consumption (Operating mode) -&gt; Quiet *8</b>	[QUIET] 1,010 W
<b>Cabinet materials</b>	Molded plastic
<b>Filter</b>	No
<b>Operation noise -&gt; Normal *3</b>	46 dB [NORMAL]
<b>Operation noise -&gt; Eco *3</b>	43 dB[ECO]

<b>Operation noise -&gt; Quiet *3</b>	46 dB [QUIET]
<b>Dimensions (W x H x D)</b>	Approx. 550 x 220 x 570 mm (21 5/8" x 8 11/16" x 22 7/16") (not including protruding parts)
<b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b>	550 mm (21 5/8")
<b>Dimensions -&gt; Height (not including protruding parts)</b>	220 mm (8 11/16")
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	570 mm (22 7/16")
<b>Weight</b>	Approx. 35 kg (77.2 lbs)
<b>Operating environment -&gt; Operating temperature *11</b>	0-45 °C (32-113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10-80 % (no condensation)
<b>Applicable software</b>	Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™
<b>Footnote Description</b>	<p>1. This is the value when the Zoom Lens (Model No.: ET-D3LES20) is used with power supply voltage of AC 200 V to AC 240 V. The value varies depending on the lens.</p> <p>2. When [OPERATING MODE] is set to [NORMAL].</p> <p>3. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.</p> <p>4. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</p> <p>5. Average light-output value of all shipped products measured at the center of the screen.</p> <p>6. Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m<sup>3</sup> of particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment.</p> <p>7. 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ24K and PT-RZ17K.</p> <p>8. Maximum value of light output is further decreased in the following cases: when a function board is installed in the slot, when the light source is deteriorating from use, or when there is dust on the optical parts.</p> <p>9. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</p> <p>10. Average value. May differ depending on the actual unit.</p> <p>11. When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0-40 °C (32-104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).</p>

<b>Body Colour</b>	Black
<b>Gross Dimensions (W x H x D in mm)</b>	RZ24KU/RZ24KEJ: 792 x 794 x 455 mm RZ24KUY/RZ24KE: 770 x 772 x 445 mm
<b>Gross Weight (Kg)</b>	RZ24KU: 44.0 kg (96.9 lbs) RZ24KUY: 42.2 kg (93.0 lbs) RZ24KE: 42.4 kg (93.6 lbs) RZ24KEJ: 44.2 kg (97.5 lbs)
<b>NFC</b>	<a href="https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional</a>
<b>EAN</b>	RZ24KEJ: 5025232925544 RZ24KE: 8887549809767