



LCD Projectors

**PT-EZ770Z/EZ770ZL/EW730Z/EW730ZL/EX800Z/EX800ZL**

**3LCD - 6,500 lumens - WUXGA - 1Lamp -  
Exchangeable lens - Digital Link - Powered H/V Lens  
Shift**

## **PT-EZ770Z/EZ770ZL**

High brightness, low TCO and flexible installation LCD Projector Ideal  
for use in education and corporate environments

### **Key Features**

---

LCD, 6,500 lumens, WUXGA

---

Daylight View Basic function ensures clear and vivid image  
quality in bright environments

---

Integrated DIGITAL LINK and Displayport connection

---

Eco filter enables up to 15,000 hours of air filter replacement  
cycle





LCD Projectors  
PT-EZ770Z/EZ770ZL/EW730Z/EW730ZL/EX800Z/EX800ZL



## PT- EZ770Z/EZ770ZL

<https://ap.connect.panasonic.com/th/en/products/projectors/pt-ez770zez770z>

<b>Projector type</b>	LCD projector
<b>Display method</b>	Transparent LCD panel (x 3, R/G/B)
<b>Display Device -&gt; Panel size</b>	19.0 mm (0.76 in) diagonal (16:10 aspect ratio)
<b>Display Device -&gt; Drive method</b>	Active matrix method
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1,920 x 1,200) x 3, total of 6,912,000 pixels
<b>Light output <sup>*1</sup></b>	6,500 lm
<b>Light output (ANSI)</b>	6,500 lm
<b>Lamp</b>	400 W UHM lamp x 1
<b>Lamp replacement cycle -&gt; NORMAL</b>	3,000 hours
<b>Lamp replacement cycle -&gt; ECO</b>	4,000 hours [ECO 1]4,500 hours [ECO 2] <sup>*2</sup>
<b>Brightness</b>	6,500 lm (lamp power: Auto/Normal, Dynamic mode, Standard lens)
<b>Resolution</b>	1,920 x 1,200 pixels
<b>Contrast Ratio (typ.) <sup>*1</sup></b>	5,000:1 (full on/full off, lamp power: Auto, iris: On)
<b>Screen size (diagonal)</b>	1.02-10.16 m (40-400 in),1.52-10.16 m (60-400 in) with the ET-ELW22,16:10 aspect ratio
<b>Center-to-corner zone ratio <sup>*1</sup></b>	90%
<b>Lens</b>	PT-EZ770Z:Powered zoom (throw ratio 1.7-2.8:1), powered focus F 1.7-2.3, f 26.9-45.4 mm EZ770ZL:Optional powered zoom/focus lenses and fixed-focus lens
<b>Lens shift -&gt; Vertical(from center of screen) <sup>*4</sup></b>	±60 % (±50 % with the ET-ELW22)from center of screen (powered)
<b>Lens shift -&gt; Horizontal(from center of screen) <sup>*4</sup></b>	±10 % from center of screen (powered)
<b>Keystone correction range</b>	Vertical ±40°, horizontal ±30°
<b>Installation</b>	Ceiling/floor, front/rear
<b>Terminals -&gt; HDMI™ IN</b>	HDMI™ 19-pin x 1 (Deep Color, compatible with HDCP), audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz/32 kHz)
<b>Terminals -&gt; DVI-D IN</b>	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP,compatible with single link only)
<b>Terminals -&gt; DisplayPort™ IN</b>	DP-20P x 1 (DisplayPort 1.1, compatible with HDCP), audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz/32 kHz)
<b>Terminals -&gt; COMPUTER IN (RGB IN )</b>	D-Sub HD 15-pin (female) x 1 (RGB/YP <sub>B</sub> P <sub>R</sub> /YC <sub>B</sub> C <sub>R</sub> x 1)
<b>Terminals -&gt; COMPUTER OUT (SUB 15pin )</b>	D-Sub HD 15-pin (female) x 1 (RGB x 1)(not compatible with all inputs)
<b>Terminals -&gt; VIDEO IN</b>	Pin jack x 1 (composite video)
<b>Terminals -&gt; AUDIO IN(M3 Stereo Mini Jack)</b>	Pin jack x 2 (L/R x 1), M3 x 2 (L-R x 2)
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	M3 x 1 (L-R x 1) for output (variable)
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals -&gt; REMOTE 1 IN</b>	M3 x 1 for wired remote control
<b>Terminals -&gt; REMOTE 1 OUT</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	RJ-45 x 1 (for network and DIGITAL LINK (video/audio/network/serial control) connection, 100Base-TX, compliant with PJLink™, HDCP compatible, Deep Color compatible)
<b>Power supply</b>	100-240 V AC, 50/60 Hz
<b>Maximum power consumption</b>	590 W (0.3 W when STANDBY MODEset to ECO*1,10 W when STANDBY MODEset to NORMAL(37 W when STANDBY MODEof AUDIO SETTING set to ON))
<b>Standby power consumption -&gt; Normal</b>	10W
<b>Standby power consumption -&gt; ECO</b>	0.3W
<b>Power consumption</b>	590 W (0.3 W when STANDBY MODEset to ECO, 10 W when STANDBY MODEset to NORMAL (37 W when STANDBY MODE of AUDIO SETTING set to ON))
<b>Built-in speaker</b>	3.7 cm round shape x 1, output power 10.0 W (monaural)
<b>Cabinet materials</b>	Molded plastic (PC + ABS)
<b>Filter</b>	Included
<b>Estimated filter maintenance cycle</b>	15,000 hours
<b>Operation noise -&gt; Normal <sup>*1</sup></b>	37 dB [NORMAL]
<b>Operation noise -&gt; Eco <sup>*3</sup></b>	31 dB [ECO1]29 dB [ECO2]
<b>Dimensions (W x H x D)</b>	PT-EZ770Z: 530 x 177*8 x 445 mm (20-7/8 x 6-31/32*8 x 17-1/2 in) (with supplied lens) EZ770ZL: 530 x 177*8 x 385 mm (20-7/8 x 6-31/32*8 x 15-5/32 in) (without lens)
<b>Dimensions -&gt; Width (including protruding parts)</b>	530 mm (20-7/8")
<b>Dimensions -&gt; Height (including protruding parts)</b>	177 mm (6-31/32")
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	PT-EZ770ZL:385 mm (15-5/32")

<b>Dimensions -&gt; Depth (including lens)</b>	PT-EZ770Z:445 mm (17-1/2")
<b>Weight *7</b>	PT-EZ770Z:Approx. 10.6 kg (23.4 lbs) (with supplied lens)PT-EZ770ZL:Approx. 9.8 kg (21.6 lbs) (without lens)
<b>Operating environment -&gt; Operating temperature *8 *9</b>	0-45 °C (32-113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10-80 % (no condensation)
<b>Footnote Description</b>	<p>* The PT-EZ770ZL/EW730ZL/EX800ZL delivers the same performance as the PT-EZ770Z/EW730Z/EX800, but comes without a lens.</p> <ol style="list-style-type: none"> <li>1. When the STANDBY MODE is set to ECO, network functions such as power on over the LAN will not operate. Also, only certain commands can be received for external control using the serial terminal.</li> <li>2. This is the maximum value when the lamp is turned on for 2 hours and off for 0.25 hours. If the lamp is turned on more times or kept on for a long time, the lamp replacement cycle will shorten. The usage environment affects the duration of the lamp.</li> <li>3. Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. Value is the average of all products when shipped.</li> <li>4. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</li> <li>5. Input signals that exceed the native resolution will be converted to the native resolution.</li> <li>6. The axis shift function cannot be used with the ET-ELW21.</li> <li>7. With the supplied lens. Value differs when the correction for both directions is operated.</li> <li>8. The usage environment affects the duration of the filter.</li> <li>9. With legs at shortest position.</li> <li>10. Average value. May differ depending on models.</li> <li>11. The operating temperature range is 0 °C to 40 °C (32 °F to 104 °F) when used at altitudes between from 1,400 m to 2,700 m (4,593 ft to 8,858 ft) above sea level. Also, if the ambient temperature exceeds 40 °C (104 °F) (35 °C (95 °F) at high altitude), the LAMP POWER may be automatically switch to Eco 2 to in order to protect the projector.</li> </ol>

<b>Body Colour</b>	White
<b>Gross Dimensions (W x H x D in mm)</b>	EZ770ZU/EZ770ZE/EZ770ZLU/EZ770ZLE: 650 x 587 x 297 mm EZ770ZE/EZ770ZLE: 644 x 581 x 297 mm
<b>Gross Weight (Kg)</b>	EZ770ZU/EZ770ZE: 16.6 kg(36.6 lbs) EZ770ZLU/EZ770ZLE: 15.8 kg(34.8 lbs) EZ770ZE: 15.5 kg(34.3 lbs) EZ770ZLE: 14.7 kg(32.5 lbs)
<b>NFC</b>	<a href="https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional</a>
<b>EAN</b>	EZ770ZE: 5025232771615 EZ770ZEJ: 5025232771622 EZ770ZLE: 5025232771660 EZ770ZLEJ: 5025232771677