



Easy-to-Manage, Super Simple 1 Chip DLP™ Laser Projector delivers Clear Pictures in Bright Rooms with Flexible Integration in diverse installation environments

PT-FRZ55

1-Chip DLP projector with 5,000 ANSI lumens and WUXGA (1920 × 1200) resolution. Fixed short-throw lens (0.8:1) with powered focus and limited lens shift (V: ±4.4%, H: ±2.1%). Supports 4K/60p signal input (displayed at WUXGA resolution). Operating noise: 32 dB (Normal), 27 dB (Quiet). Compact and lightweight at approx. 16.4 kg with dimensions of approx. 400 x 160 x 181 mm. Colour black.

Key Features

Laser 1-chip DLP, 5,000 lumens, WUXGA

DLP™ imaging technology, Quartet Colour Harmonizer, Rich Colour Enhancer, and digitally modulated Dynamic Contrast 2 optimization

Maintenance free up to 20,000 hours with dust-resistant optical block and long lasting laser engine

0.8:1 short-throw lens

Supports uncompressed 4K/60p input signals via HDCP 2.2-compliant HDMI® inputs or DIGITAL LINK terminal





PT-FRZ55

<https://ap.connect.panasonic.com/vn/en/products/projectors/pt-frz55>

Projector type	1-Chip DLP™ projector
Display method	DLP™ chip x 1, DLP™ projection system
Display Device -> Panel size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)
Display Device -> Number of pixels	2,304,000 (1920 x 1200 pixels)
Light source	Laser diodes
Light output *1 *2 *3	5,000 lm
Light output (ANSI) *4	5,000 lm
Light output (Center) *5	5,200 lm (Center)
Time until light output declines to 50 %	20,000 hours [NORMAL]
-> NORMAL *6	
Resolution	1920 x 1200 pixels
Contrast Ratio (typ.) *3	20,000:1 (Full On/Full Off, Picture Mode: Dynamic, Dynamic Contrast 1, Operating Mode: Normal)
Screen size (diagonal)	1.02–7.62 m (40–300 in), 16:10 aspect ratio
Center-to-corner zone ratio *3	85%
Lens	Fixed (throw ratio: 0.8:1), powered focus, F 1.75, f 11.9 mm
Lens shift -> Vertical(from center of screen)	±4.4 % (powered)
Lens shift -> Horizontal(from center of screen)	±2.1 % (powered)
Keystone correction range	Vertical: ±25 °, Horizontal: ±20 °
Installation	Ceiling/floor, front/rear, free 360-degree installation
Terminals -> HDMI™ IN	HDMI™ 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input*4), CEC supported
Terminals -> COMPUTER IN (D-SUB 15pin)	D-sub HD 15-pin (female) x 1 (RGB/Y/P _R /Y/C _B /C _R)
Terminals -> COMPUTER OUT (D-SUB 15pin)	D-sub HD 15-pin (female) x 1 (RGB/Y/P _R /Y/C _B /C _R)
Terminals -> VIDEO IN	Pin jack x 1 (composite video)
Terminals -> AUDIO IN(M3 Stereo Mini Jack)	Pin jack x 1 (L, R)
Terminals -> AUDIO IN(Pin Jack L/R)	M3 x 1 / M3 x 1
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	M3 x 1 (Variable)
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals -> DIGITAL LINK IN / LAN	RJ-45 x 1 for network and DIGITAL LINK connections (HDBaseT™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.3 compatible, Deep Color compatible, 4K/60p signal input*4
Terminals -> LAN	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals -> USB TYPE A	USB connector (Type A) x 1 (Output 5 V/2 A)
Power supply	AC 100–240 V, 50/60 Hz
Maximum power consumption *7	465 W (5.0–2.0 A)
On-mode power consumption(Operating mode) -> Normal *8	[NORMAL] 370 W
On-mode power consumption(Operating mode) -> Eco *8	[ECO] 295 W
On-mode power consumption(Operating mode) -> Quiet *8	[QUIET] 295 W
Standby power consumption -> Normal	10 W (Standby Mode) [NORMAL]
Standby power consumption -> ECO	0.5 W (Standby Mode) [ECO]
Cabinet materials	Molded plastic
Filter	No
Operation noise -> Normal *3	32 dB [NORMAL]
Operation noise -> Quiet *3	27 dB [QUIET]
Dimensions (W x H x D)	Approx. 498 x 168 ^{*7} x 481 mm (19 5/8" x 6 5/8" ^{*7} x 18 15/16")
Dimensions -> Width (including protruding parts)	498 mm (19 5/8")
Dimensions -> Height (including protruding parts)	168 mm (6 5/8")
Dimensions -> Depth (including lens)	481 mm (18 15/16")
Weight	Approx. 16.4 kg (36.1 lbs)
Operating environment -> Operating temperature *11	0–45 °C (32–113 °F)

Operating Environment -> Operating humidity (No condensation)	10–80 % (no condensation)
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software
Body Colour	Black
NFC	No
Terminals -> SDI IN	—
Terminals -> DVI-D IN	—
Terminals -> DisplayPort™ IN	—
Operation noise -> Eco *3	—
Gross Dimensions (W x H x D in mm)	FRZ55B: Approx. 684 x 291 x 596 mm FRZ55BEJ: Approx. 694 x 310 x 606 mm
Gross Weight (Kg)	FRZ55B: 21.1 kg (46.4 lbs) FRZ55BEJ: 22.6 kg (49.9 lbs)
Active 3D	No
SDM	No
EAN	FRZ55B: 5025232941445 FRZ55BEJ: 5025232941452
Footnote Description	<ol style="list-style-type: none"> 1. When [PICTURE MODE] is set to [DYNAMIC], [DAYLIGHT VIEW] is set to [OFF], [DYNAMIC CONTRAST] is set to [OFF], [LIGHT OUTPUT] is set to [100%], and [AUTO POWER SAVE] is set to [OFF]. 2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118:2020 international standards. Value is the average of all products when shipped. 3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. 4. Average light-output value of all shipped products measured at the center of the screen. 5. Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast 2, temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of airborne particulate matter. Estimated time until light output declines to 50 % varies depending on environment. 6. 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. 7. With legs at shortest position. 8. Average value. May differ depending on the actual unit.