



Designed for long-lasting stable brightness in events and staging. Laser light source, 3-chip DLP, 12 000 lumens, WUXGA projector.

## PT-RZ12K

Compact 12 000 lumens Solid Shine laser Projector Designed for long-lasting stable brightness in events and staging Exchangeable lens - 24/7 Operation, Digital Link, High Frame Rate 120 Hz, Geometric Adjustment, Portrait Mode, Digital Link, 20 000:1

### Key Features

Laser 3-chip DLP, 12000 lumens, WUXGA

120Hz high frame rate for superb and sharp motion pictures

Lamp-free laser projection and dust resistant liquid cooling system with 20000 hours of free maintenance

20,000:1 contrast ratio





## PT-RZ12K

<https://ap.connect.panasonic.com/vn/en/products/projectors/pt-rz12k>

<b>Projector type</b>	3-Chip DLP™ projector
<b>Display method</b>	DLP™ chip x 3, DLP™ projection system
<b>Display Device -&gt; Panel size</b>	PT-RZ12K : 24.4 mm (0.96") diagonal (16:10 aspect ratio)PT-RS11K : 24.1 mm (0.95") diagonal (4:3 aspect ratio)
<b>Display Device -&gt; Number of pixels</b>	PT-RZ12K : 2,304,000 (1920 x 1200) x 3, total of 6,912,000 pixelsPT-RS11K : 1,470,000 (1400 x 1050) x 3, total of 4,410,000 pixels
<b>Light source</b>	Laser diode (Class 1)
<b>Light output *1 *2</b>	12,000 lm
<b>Time until light output declines to 50 % -&gt; NORMAL *5</b>	20,000 hours [NORMAL]
<b>Time until light output declines to 50 % -&gt; ECO *5</b>	24,000 hours [ECO]
<b>Time until light output declines to 50 % -&gt; QUIET *5</b>	20,000 hours [QUIET]
<b>Resolution</b>	PT-RZ12K : 1920 x 1200 pixelsPT-RS11K : 1400 x 1050 pixels
<b>Contrast Ratio (typ.) *2</b>	20,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)
<b>Screen size (diagonal)</b>	1.78–25.4 m (70–1,000"), 1.78–15.24 m (70–600")with the ET-D75LE8, 3.05–15.24 m (120–600")with the ET-D75LE90, 16:10 aspect ratio1.78–25.4 m (70–1,000"), 1.78–15.24 m (70–600")with the ET-D75LE8, 3.05–15.24 m (120–600")with the ET-D75LE90, 4:3 aspect ratio
<b>Refresh rate</b>	120 Hz*3
<b>Lens</b>	Optional powered zoom and fixed-focus lenses
<b>Lens shift -&gt; Vertical(from center of screen) *6</b>	±55 % (±44 % with the ET-D75LE6, +73 – +78 % with the ET-D75LE90) (powered)±50 % (±40 % with the ET-D75LE6, +71 % with the ET-D75LE90) (powered)
<b>Lens shift -&gt; Horizontal(from center of screen) *6</b>	±20 % (±15 % with the ET-D75LE6, ±6 % with the ET-D75LE90) (powered)±30 % (±20 % with the ET-D75LE6) (powered)*8
<b>Keystone correction range</b>	Vertical: ±40° (±22° with ET-D75LE50, ±28° with ET-D75LE6, +5° with ET-D75LE90), horizontal: ±15° (0° with ET-D75LE90)
<b>Keystone correction range with optional ET-UK20 Upgrade Kit *6</b>	Vertical: ±45° (±40° with ET-D75LE10/ET-D75LE20, ±22° with ET-D75LE50, ±28° with ET-D75LE6, +5° with ET-D75LE90), horizontal: ±40° (±15° with ET-D75LE50/ET-D75LE6, 0° with ET-D75LE90)
<b>Installation</b>	Ceiling/floor, front /rear, free 360-degree installation
<b>Power supply</b>	100–240 V AC, 50/60 Hz
<b>Maximum power consumption</b>	1,200 W (1,280 VA) Average power consumption: 800 W (Normal Mode), 680 W (Eco Mode), 620 W (Long Life 1 Mode), 590 W (Long Life 2 Mode), 550 W (Long Life 3 Mode)
<b>Standby power consumption -&gt; Normal</b>	4 W [NORMAL]
<b>Standby power consumption -&gt; ECO</b>	0.3 W [ECO]*2
<b>Cabinet materials</b>	Molded plastic
<b>Filter</b>	No
<b>Operation noise -&gt; Normal *2</b>	43 dB [NORMAL]
<b>Dimensions (W x H x D)</b>	578 x 270 x 725 mm (22 3/4" x 10 5/8" x 28 17/32") (optional lens, legs and lens cover not included), 578 x 323.5 x 740 mm (22 3/4" x 12 23/32" x 29 1/8") (Including legs at shortest position and protruding parts)
<b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b>	578 mm (22 3/4")
<b>Dimensions -&gt; Width (including protruding parts)</b>	578 mm (22 3/4")
<b>Dimensions -&gt; Height (not including protruding parts)</b>	270 mm (10 5/8")
<b>Dimensions -&gt; Height (including protruding parts)</b>	323.5 mm (12 23/32")
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	725 mm (28 17/32")
<b>Dimensions -&gt; Depth (including lens)</b>	740 mm (29 1/8")
<b>Weight *8</b>	Approx. 44.0 kg (97 lbs) (optional lens not included)
<b>Operating environment -&gt; Operating temperature *9</b>	0–50 °C (32–122 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10–80 % (no condensation)
<b>Applicable software</b>	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit and ET-CUK10 Auto Screen Adjustment Kit)
<b>Body Colour</b>	Black
<b>Gross Dimensions (W x H x D in mm)</b>	RZ12KU/RZ12KUY/RZ12KEJ: 824 x 964 x 399 mm RZ12KE: 810 x 950 x 418 mm

<b>Gross Weight (Kg)</b>	RZ12KU/RZ12KUY: 53.4 kg (117.7 lbs) RZ12KE: 51.9 kg (114.4 lbs) RZ12KEJ: 54.0 kg (119.1 lbs)
<b>NFC</b>	<a href="https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartpjcontrol/regional.html#regional</a>
<b>EAN</b>	RZ12KE: 5025232829439 RZ12KEJ: 5025232829446
<b>Footnote Description</b>	<ol style="list-style-type: none"> <li>1. Operating temperature: 25 °C (77 °F), altitude: 700 m (22 ft 12 in), ICE627087: 2008 Broadcast Content, Image Mode: Dynamic, Dynamic Contrast Mode: 3.</li> <li>2. When Standby Mode is set to Eco, network functions such as power on over LAN will not operate. Additionally, only certain commands can be received for external control using the serial terminal.</li> <li>3. Refresh rate varies depending on scanning frequency.</li> <li>4. At this time the brightness will have decreased to approximately half of its original level. Operating Temperature: 35 °C (95 °F), Altitude 700 m (22 ft 12 in), Dust: 0.15 mg/m3.</li> <li>5. Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards.</li> <li>6. Input signals that exceed the native resolution will be converted to the native resolution.</li> <li>7. Optical axis shift function cannot be operated when used with the ET-D75LE50.</li> <li>8. Range varies depending on mounted lens.</li> <li>9. Average value. May differ depending on the actual unit.</li> <li>10. When operational mode is set to Normal, operating temperature is from 0 °C (32 °F) to 50 °C (122 °F), and operating temperature is from 0 °C (32 °F) to 45 °C, (113 °F) when used in locations from 1,400 m to 4,200 m (4,593 ft to 13,780 ft) above sea level. When operational mode is set to Eco or Long Life 1/2/3, operating temperature is from 0 °C (32 °F) to 45 °C (113 °F). When used with Smoke Cut Filter, operating temperature is from 0 °C (32 °F) to 40 °C (104 °F). Projector cannot be used in locations over 2,700 m (8,858 ft) with operational mode set to Eco or Long Life 1/2/3. When used with Smoke Cut Filter, the projector cannot be used in locations over 1,400 m (4,593 ft). Light source brightness may decrease depending on operating temperature. When projector is operating at high temperature, brightness will decrease correspondingly.</li> </ol>