



Build-up Unit - Supports Large and ENG/EPF lens adaptor

AK-HBU500

Build-up Unit - Supports Large and ENG/EPF lens adaptor

Key Features

Camera can be mounted fast and smoothly

One cable solution

Power Output: DC12V/7.5A and DC12V/1.5A

3 User buttons

3 Cursor memories/button



AK-HBU500

<https://ap.connect.panasonic.com/vn/en/ak-hbu500>

General -> Power Supply	12 V DC (when external power is supplied) 240 V AC 50 Hz/60 Hz (when UCU is connected)
General -> Power Consumption	70 W (when external power is supplied) 165 W (when UCU is connected)
General -> Operating Temperature	-10°C to 45°C (14°F to 113°F)
General -> Operating Humidity	85% or less (relative humidity)
General -> Storage Temperature	-20°C to 60°C (-4°F to 140°F)
General -> Weight	Approx. 12.8 kg (28.22 lb) (unit only)
General -> Dimensions	W 300 mm x H 417 mm x D 510 mm (16-7/16 inches x 20-1/16 inches x 11-13/16 inches)
Input/Output -> LENS I/F Connector	36-pin x 1
Input/Output -> CAMERA I/F Connector	20-pin x 1
Input/Output -> [DC IN] Connector	XLR x 1, 4-pin, 12 V DC
Input/Output -> [DC OUT 12 V 1.5 A] Connector	4-pin x 1
Input/Output -> [DC OUT 12 V 7.5 A] Connector	XLR x 1, 4-pin
Display Part -> Camera Number Display	1 to 15 (depending on system settings)