



**Build-up Unit - Supports Large and ENG/EPF lens adaptor**

## **AK-HBU500**

Build-up Unit - Supports Large and ENG/EPF lens adaptor

### **Key Features**

---

Camera can be mounted fast and smoothly

---

One cable solution

---

Power Output: DC12V/7.5A and DC12V/1.5A

---

3 User buttons

---

3 Cursor memories/button



## AK-HBU500

<https://ap.connect.panasonic.com/vn/en/ak-hbu500>

|                                    |   |
|------------------------------------|---|
| <b>Power Supply</b>                | 12 V DC (when external power is supplied)<br>240 V AC 50 Hz/60 Hz (when AK-UCU500 is connected)   |
| <b>Power Consumption</b>           | 70 W (when external power is supplied)<br>165 W (when AK-UCU500 is connected)   |
| <b>Operating Temperature</b>       | -10°C to 45°C (14°F to 113°F)   |
| <b>Operating Humidity Range</b>    | 85% or less (relative humidity)   |
| <b>Storage Temperature</b>         | -20°C to 60°C (-4°F to 140°F)   |
| <b>Weight</b>                      | Approx. 12.8 kg (28.22 lb) (unit only)  |
| <b>Dimensions (W x H x D)</b>      | 300 mm x 417 mm x 510 mm<br>(16-7/16 inches x 20-1/16 inches x 11-13/16 inches)   |
| <b>Camera Number Display</b>       | 1 to 15 (depending on system settings)  |
| <b>Lens I/F Connector</b>          | 36-pin x 1  |
| <b>Camera I/F Connector</b>        | 20-pin x 1  |
| <b>[DC In] Connector</b>           | XLR x 1, 4-pin, 12 V DC   |
| <b>[DC Out 12V 1.5A] Connector</b> | 4-pin x 1   |
| <b>[DC Out 12V 7.5A] Connector</b> | XLR x 1, 4-pin  |
| <b>Note</b>                        | <p>*1: Depending on the setting, only one of them can be selected at one time.</p> <p>*2: The BB (black burst) signal and tri-level sync signal of the reference input are recognized automatically.</p> <p>*3: IP video cannot be transmitted when [CCU MODE] is set to [2160/23.98p], [2160/23.98PsF], [1080/23.98p], or [1080/23.98PsF].</p> <p>*4: Can be provided from CCU</p> |