



**Build-up Unit - Supports Large and ENG/EPF lens adaptor**

## **AK-HBU500**

Build-up Unit - Supports Large and ENG/EPF lens adaptor

### **Key Features**

---

Camera can be mounted fast and smoothly

---

One cable solution

---

Power Output: DC12V/7.5A and DC12V/1.5A

---

3 User buttons

---

3 Cursor memories/button



## AK-HBU500

<https://ap.connect.panasonic.com/vn/vi/ak-hbu500>

<b>General -&gt; Power Supply</b>	12 V DC (when external power is supplied) 240 V AC 50 Hz/60 Hz (when UCU is connected)
<b>General -&gt; Power Consumption</b>	70 W (when external power is supplied) 165 W (when UCU is connected)
<b>General -&gt; Operating Temperature</b>	-10°C to 45°C (14°F to 113°F)
<b>General -&gt; Operating Humidity</b>	85% or less (relative humidity)
<b>General -&gt; Storage Temperature</b>	-20°C to 60°C (-4°F to 140°F)
<b>General -&gt; Weight</b>	Approx. 12.8 kg (28.22 lb) (unit only)
<b>General -&gt; Dimensions</b>	W 300 mm x H 417 mm x D 510 mm (16-7/16 inches x 20-1/16 inches x 11-13/16 inches)
<b>Input/Output -&gt; LENS I/F Connector</b>	36-pin x 1
<b>Input/Output -&gt; CAMERA I/F Connector</b>	20-pin x 1
<b>Input/Output -&gt; [DC IN] Connector</b>	XLR x 1, 4-pin, 12 V DC
<b>Input/Output -&gt; [DC OUT 12 V 1.5 A] Connector</b>	4-pin x 1
<b>Input/Output -&gt; [DC OUT 12 V 7.5 A] Connector</b>	XLR x 1, 4-pin
<b>Display Part -&gt; Camera Number Display</b>	1 to 15 (depending on system settings)